



WM588

Mobile Radio

As a mobile radio with thin and stylish design, totally functionality, WM588 which is compatible with both analog and digital modes brings extraordinary experience of communication in variety of scenarios such as taxis, truck, freight cars, school buses, delivery and ambulance.



WM588 DMR Mobile Radio

Key Features and Benefits

• Compact, Sophisticated and Stylish

Fashionable design, only 151mm×149mm×47mm in size and weighs 1.15kg with a 1.8" color HD TFT screen.

• Smart Digital-Analog Auto Detection

WM588 can be configured in analog, digital or mixed mode. When configured in mixed mode, the mobile dynamically switch mode depending on the type of signal received.

• Versatile Voice Calls

Enhanced digital voice call feature facilitates call management between team members and ensures communication privacy.

• Secure Communication

WM588 provides basic and enhanced encryption capability using ARC4 algorithm. It ensures secure communication on voice call and data transfer between team members. DES, and 256 bits AES encryption algorithm are optional.

• Roaming

Automatic roaming helps you to use the radio freely among all sites on an IP Multi-Site Connect system.

• Versatile Services

In addition to conventional communication services, WM588 provides multiple functions such as Text Message, Radio Enable/Disable, Remote Monitor, Kill and Emergency calls.

• Enhanced Noise Cancellation

WM588 is equipped with enhanced noise cancellation to provide clear voice communication, whether the signal is digital or analogue.

• Pseudo Trunk

Dynamically allocation of slot while using repeater mode. Improve channel utilization providing simultaneous communication on radios.

• GPS Location (Optional)

Integrated GPS enables the real time tracking of the mobile working team.

• Bluetooth Connectivity

Built-in bluetooth for WM588 enables users to communicate with others through a bluetooth earpiece.


Standard Accessories



Hand Microphone



Mounting Bracket



Power Cord

Optional Accessories



Hand Microphone
(with keypad)



Vehicle Antenna



GPS Antenna

Specifications

General

Frequency Range	136~174MHz,400~470MHz
Channel Capacity	256
Zone Capacity	16
Channel Spacing	20kHz/25kHz/12.5kHz
Operating Voltage	13.6V±15%
Current Drain	Standby <0.6A Receive <2.0A Transmit <8A(25W)
Frequency Stability	0.5ppm
Antenna Impedance	50Ω
Dimensions(H·W·D)	151mm×149mm×47mm
Weight	1.15kg
LCD Display	1.8inch, 5 rows

Receiver

Sensitivity	Analog 0.16uV@12dB SINAD(Typical) Digital 0.18uV@BER5%(Typical)
Selectivity	60dB@12.5kHz, 70dB@20/25kHz(TIA-603) 60dB@12.5kHz, 70dB@20/25kHz(ETSI)
Spurious Response Rejection	70dB@12.5/20/25kHz(TIA-603) 70dB@12.5/20/25kHz(ETSI)
Inter-modulation	70dB@12.5kHz/25kHz(TIA-603) 65dB@12.5kHz/25kHz(ETSI)
Hum and Noise	40dB@12.5kHz, 45dB@20/25kHz
Rated Audio Power Output	3W
Rated Audio Distortion	3% (Typical)
Audio Response	+1~-3dB
Conducted Spurious Emission	-57dBm@<1GHz, -47dBm@>1GHz

Transmitter

RF Power Output	Low Power:5W, High Power: 25W
FM Modulation	11K0F3E@12.5kHz, 14K0F3E@20kHz, 16K0F3E@25kHz
4FSK Digital Modulation	12.5kHz Data: 7K60F1D&7K60FXD, 12.5kHz Voice: 7K60F1E&7K60FXE, Combination of 12.5kHz Voice and Data: 7K60F1W
Modulation Limiting	±2.5kHz@12.5kHz, ±4.0kHz@20kHz, ±5.0kHz@25kHz
FM Hum & Noise	40dB@12.5kHz, 45dB@20kHz/25kHz
Adjacent Channel Power	60dB@12.5kHz, 70dB@20kHz/25kHz
Audio Response	+1~-3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE+2™
Digital Protocol	ETSI-TS 102 361-1,-2,-3

GPS

Accuracy specs are for long-term tracking(5 satellites visible at nominal-130dBm)

TTFF(Time To First Fix)-Cold Start	<1 minute
TTFF(Time To First Fix)-Hot Start	10 seconds
Horizontal Accuracy	10 m

Environmental Specifications

Operating Temperature	-30 C ~+60 C
Storage Temperature	-40 C ~+85 C
ESD	IEC610000-4-2(Level4) ±4kV(Contact) ±8kV(air)
American Military Standard	MIL-STD-810-C/D/E/F/G
Dust & Water Protection	IP54 Standard
Humidity	Per MIL-STD-810 C/D/E/F/G Standard
Shock & Vibration	Per MIL-STD-810 C/D/E/F/G Standard

All specifications are subject to change without notice due to continuous development.